

# Novax Class 4 Specification Sheet

## NOVAX RUBBER INSULATING GLOVES

### PRODUCT DESCRIPTION:

Novax rubber electrical insulating gloves, class 4, 18-inch.

- Meet ANSI/ASTM D120 standard and NFPA 70E for use around electrical hazards and arc flash protection.
- Contoured shape reduces hand fatigue.
- Natural rubber construction offers the required dielectric properties combined with flexibility, strength and durability.
- Silicone free.

### Applications:

Used exclusively for electrical purposes, such as utilities and electrical contractors.

### TECHNICAL DATA:

Shell: Natural rubber

Color: Black (150); Black with orange liner (155)

Cuff Style: Rolled

Available Sizes: 8-12 (150); 9-12 (155)

Packaging: 1 pair per box, 12 pair per case

Case Dimensions: (cm) - 53.7 x 46.1 x 30.2 / (in) - 21.1 x 18.1 x 11.9

Case Weight: 35.3 lbs / 16.0 kg

Country of Origin/Harmonization Code: Malaysia/4015.19.1050

Certifications: ISO 9001:2003

### MAX USE VOLTAGE:

	AC V rms	DC V
Class 4	36,000	54,000

**10** NOVAX™ by G.B. INDUSTRIES  
ANSI / ASTM CLASS 4 MADE IN MALAYSIA D120 TYPE I  
MAX USE VOLT 36000V AC

BARCODE #	BOX	CASE
150-4-18/8	01616314064592	02616314064591
150-4-18/9	01616314064585	02616314064584
150-4-18/10	01616314064608	02616314064607
150-4-18/11	01616314064615	02616314064614
150-4-18/12	01616314064622	02616314064621
155-4-18/9	01616314063717	02616314063716
155-4-18/10	01616314063724	02616314063723
155-4-18/11	01616314063731	02616314063730
155-4-18/12	01616314063748	02616314063747



### DIMENSIONS:

Size Available	8	9	10	11	12
Over Length (cm) - A	46.0	46.0	46.0	46.0	46.0
(in)	18.0	18.0	18.0	18.0	18.0
Palm Width (cm) - B	10.0	10.5	12.0	13.5	15.0
(in)	3.9	4.1	4.7	5.3	5.9
Max thickness (mm)	3.5	3.5	3.5	3.5	3.5

