

Highlander™ Plus

ANSI • CE • CSA • Ballistic •



FOAM
PADDING



INCLUDES
STRAP



VENTED
FRAME



MIL-PRF-
32432

Removable indirect vented flame resistant foam carriage // Detachable strap // Passes Ballistic MIL-PRF-32432 High Velocity Impact standards // Custom imprinting available



Black and Gray Frame | 5 Variations

- SBG5010DT ●●● Clear **H2X** AF
- SBG5020DT ●●● Gray **H2X** AF
- SBG5030DT ●●● Amber **H2X** AF
- SBG5055DT ●●● Sky Red Mirror AF
- SBG5080DT ●●● I/O Mirror AF

i Highlander Plus is partially foam padded which allows for airflow.

Part No.	Lens Marking	Temple Marking	General Specifications	Materials
SBG5010DT	P+U6	P Z87 + / P c SEI Z94.3	Weight: 36 gm	Lens: polycarbonate
SBG5020DT	P+U6 L2.5	P Z87 + / P c SEI Z94.3	PD: 68 mm	Frame: nylon
SBG5030DT	P+U6	P Z87 + / P c SEI Z94.3	Bridge: 9 mm	Temples: polycarbonate & nylon
SBG5055DT	P+S	P Z87 + / P c SEI Z94.3	Lens base: 8 curve	Hinge: polycarbonate & nylon
SBG5080DT	P+U6 L1.7	P Z87 + / P c SEI Z94.3	Lens size diagonal: 68.4 mm	Screw: stainless steel

Lens Marking Symbols

P: Manufacturer's mark
 +: High impact
 S: Special Purpose
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light
 L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices

Lens size vertical: 49 mm
 Lens thickness: 2.3 mm
 Overall length (lens - tip): 166 mm
 Overall width (hinge - hinge): 136.5 mm
 Closest point between temple tips: 80 mm
 Closest point between lens: 15.6 mm
 Nosepiece: polyvinyl chloride (PVC)
 Strap: polyester
 Strap holder: polyethylene (POM)