

Capstone® 600 Series



Gray Goggle with Adjustable Strap

Part Lens
 EG604T2 ••••• Clear H2X Anti-Fog

- Fits over prescription glasses.
- Indirect ventilation system prevents fogging.
- Includes interchangeable cloth and neoprene straps.
- Co-material goggle provides superior protection against dust entry and chemical splash.
- Thermoplastic (TPE) body with universal nose bridge is flexible and contours to the user's face.

GENERAL SPECIFICATION
Bridge: 45mm
Lens Base: 6 curve
Lens Size Diagonal: 167mm
Lens Size Vertical: 74.1mm
Lens Thickness: 2.3mm
Overall Length (Lens-Tip): 90mm
Overall Width (Hinge-Hinge): 160mm
PD: 68mm
Weight: 84gm
Closest point between lens: N/A
Closest point between strap holding parts: 150mm
Strap Length: 540mm

Capstone® 600 Series

PACKAGING
Hi-Density PE bag: 1pc
Display Box: 1 pc
Outer Carton: 72 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	6 base single lens
Body	Hard piece	PP
	Soft piece	TPE
Frame insert	TPV	Co-material body with flexible soft flange contour to face
Strap Holder	Cloth strap (option 1)	Nylon
	Plastic strap (option 2)	NR + SBR
Headband	Cloth Strap (option 1)	Polyester
	Plastic strap (option 2)	
Nose piece	TPE	Soft insert with 6 holes engaged between lens and frame body to make indirect vents for airflow
		Strap sewed with quick-released parts
		Strap clipped on the holder
		Adjustable quick-released textile elastic fixed on strap holders
		Universal, integral to frame body (soft piece)

PART	LENS	LENS MARKING	FRAME MARKING
EG604T2	 Clear H2X Anti-Fog	2C - 1.2 P 1 BT N CE	CE P EN166 3 4 BT

LENS MARKING

Code (field of use):

2 or 3: UV Filter
5 or 6: Solar Filter

Color Perception:

C: Unimpaired color perception

Protection Class:

1.2 to 6: Degree of visible light filtration

Optical Class:

1: High optical quality / No optical distortion

Mechanical Strength:

S: Extra strong, resists a 22mm, 43g ball falling 1.30 m/s
F: Low energy impact, resists a 6mm, 0.86g at 45 m/s
B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s
A: High energy impact, resists a 6mm, 0.86g at 190 m/s

Symbols:

P: Manufacture Indication
N: Filter with Anti-Fog features
CE: European Standard

FRAME MARKING

Symbols:

CE: European Standard
P: Manufacture Indication
EN166: CE specification for protective eyewear

Mechanical Strength:

F: Low energy impact
B: Medium energy impact
BT: Medium energy impact at extreme temperatures

Protection Class:

3: Protection against liquid droplets
4: Protection against large dust

EN SEGURIDAD

Equipos de Protección Personal