

EMERGE®

STYLISH DUAL FRAME WITH FULL EYE PROTECTION



Black Frame

Part	Lens
SB7910DRX●●●	<input type="checkbox"/> Clear
SB7910D15●●	<input type="checkbox"/> Clear +1.5
SB7910D20●●	<input type="checkbox"/> Clear +2.0
SB7950SF●●	<input type="checkbox"/> 5.0 IR
SB7960SF●●	<input type="checkbox"/> 3.0 IR

Translucent Gray Frame

Part	Lens
SG7910DRX●●●	<input type="checkbox"/> Clear
SG7910D15●●●	<input type="checkbox"/> Clear +1.5
SG7910D20●●●	<input type="checkbox"/> Clear +2.0

Translucent Caramel Frame

Part	Lens
STC7910DRX●●●	<input type="checkbox"/> Clear
STC7910D15●●●	<input type="checkbox"/> Clear +1.5
STC7910D20●●●	<input type="checkbox"/> Clear +2.0

- Suitable for both working environments and sports activities.
- Soft nose piece provides comfort for extended use without slipping.
- Stylish dual lens with full eye protection, plano lens, prescription lens, and full reader lens adaptable.
- Will accommodate an Rx lens to the maximum of +3 to -3 diopters.

GENERAL SPECIFICATION

Bridge: 13mm
Closest Point Between Lens: 17.7mm
Closest Point Between Temple Tips: 83mm
Lens Base: 6 Curve
Lens Size Diagonal: 58mm
Lens Size Vertical: 42.5mm
Lens Thickness: 2.2mm
Overall Length (Lens-Tip): 163mm
Overall Width (Hinge-Hinge): 135mm
PD: 68mm
Weight: 30gm

PACKAGING












Polybag: 1pc

Inner Box: 12 pcs

Case: 300 pcs

EMERGE®**STYLISH DUAL FRAME WITH FULL EYE PROTECTION**

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	6 base curve, dual lens frame style
Frame	G300 Nylon	Wrap around design with wide temples for extended side protection
Nose piece	PVC	Glued onto the nose bridge, pillow softness
Temple	Polycarbonate	Spatula Type
Hinge	Polycarbonate	3 barrel type, integral to frame/temple
Screw	Stainless Steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
SB7910DRX	 Clear	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB7910D15	 Clear +1.5	P + U6	P Z87 + 1.5
SB7910D20	 Clear +2.0	P + U6	P Z87 + 2.0
SB7950SF	 5.0 IR	P +	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB7960SF	 3.0 IR	P +	P Z87 + / P c SEI CAN/CSA Z94.3-07
SG7910DRX	 Clear	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-07
SG7910D15	 Clear +1.5	P + U6	P Z87 + 1.5
SG7910D20	 Clear +2.0	P + U6	P Z87 + 2.0
STC7910DRX	 Clear	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-07
STC7910D15	 Clear +1.5	P + U6	P Z87 + 1.5
STC7910D20	 Clear +2.0	P + U6	P Z87 + 2.0

LENS MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

W: Welding Filter

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

+1.5, 2.0: Rx

P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices