

Exeter® ANSI • CE •



RUBBER NOSEPIECE



CO-INJECTED TEMPLES

Built-in rubber nosepiece //
Co-injected rubber temples
// Extended lens // Custom
imprinting available

Glossy Black Frame | 7 Variations

- SB 5110DT •• Clear **H2X** AF
- SB 5120DT •• Gray **H2X** AF
- SB 5133DT • Shooter's Amber **H2X** AF
- SB 5155DT •• Sky Red Mirror AF
- SB 5170DT •• Silver Mirror AF
- SB 5175DT •• Blue Mirror AF
- SB 5180DT • I/O Mirror AF



Part No.	Lens Marking	Temple Marking	General Specifications	Materials
SB 5110DT	P Z87 + U6	P Z87 +	Weight: 29 gm	Lens: polycarbonate
SB 5120DT	P Z87 + U6 L2.5	P Z87 +	PD: 68 mm	Frame: nylon
SB 5133DT	P Z87 + S	P Z87 +	Bridge: 13.4 mm	Temples: nylon + polyvinyl chloride (PVC)
SB 5155DT	P Z87 + S	P Z87 +	Lens base: 8 curve	Hinge: nylon
SB 5170DT	P Z87 + S	P Z87 +	Lens size diagonal: 70.8 mm	Screw: stainless steel
SB 5175DT	P Z87 + S	P Z87 +	Lens size vertical: 44 mm	Nosepiece: polyvinyl chloride (PVC)
SB 5180DT	P Z87 + U6 L1.7	P Z87 +	Lens thickness: 2.3 mm	

Lens Marking Symbols

P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices

+: High impact

S: Special Purpose

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light

L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices

+: High impact

c SEI Z94.3: CAN/CSA standard for eye and face protection devices

General Specifications

Weight: 29 gm
PD: 68 mm
Bridge: 13.4 mm
Lens base: 8 curve
Lens size diagonal: 70.8 mm
Lens size vertical: 44 mm
Lens thickness: 2.3 mm
Overall length (lens - tip): 157 mm
Overall width (hinge - hinge): 127.5 mm
Closest point between temple tips: 93 mm
Closest point between lens: 14.8 mm